

# INSTRUCTIONS.

## SET CONTENT.

1x 100 ml SPECIAL CLEANER TOP-CLEAN COLOR \*

1x 100 ml PV-GARD PRESERVATIVE\*

1x 30 ml SEAL CARE AGENT

1x 30 ml FITTING OIL

1x Cleaning cloth

## INSTRUCTIONS.

Please observe our extensive operating, care and maintenance instructions – you can download them at [gaulhofer.com/service](http://gaulhofer.com/service).

Shake cleaning agent before use.

Do not clean surfaces in direct sunlight, the surface temperature should not exceed 25 °C. Only use pH neutral, non-scratching and non-scouring cleaning agents.

### \*Ingredients:

< 5% non-ionic surfactants. Further information: Phenoxyethanol.

### \*Safety recommendations:

P101 Should you be required to seek medical attention, have packaging or identification label ready.

P102 Keep out of reach of children. Safety data sheet is available upon request for commercial users.

Should you have any questions regarding use, care or maintenance and to order additional maintenance and care products, please directly contact your GAULHOFER professional partner.

Version: 06/2016 – Subject to errors and changes.

# CARE SET.

To clean and treat wood, wood-aluminium, uPVC and uPVC-aluminium windows and doors.

**GAULHOFER** elements are high-quality products and designed for long service life.

To preserve their faultless surface, permanent operating comfort and tightness, one needs to regularly clean, treat and maintain these building elements.

Apart from the weather, exterior building elements also need to withstand stress caused by smoke, industrial emissions, airborne dust and more. Together with rain and condensation, contamination and deposits of this kind can damage their surface and impede their visual appearance.

You can find comprehensive instructions on the operation, care and maintenance in the **GAULHOFER Manual** of the same name. Helping you enjoy your GAULHOFER elements for decades to come!

### QUALITY FOR A LIFETIME.



# USAGE INSTRUCTIONS.

Please observe correct order!

## 1. TOP-CLEAN COLOR CLEANER.

### Area of application:

This special cleaner removes minor to major contamination from all painted and metallic-coated aluminium surfaces, glazed and painted wood as well as hard, white and foiled uPVC. Note: Not suited for stainless steel and hand-oiled surfaces.

### Application:

Put Top-Clean Color onto a lint-free cotton cloth and clean surfaces carefully using mild pressure, dry with a cotton cloth.

[Attention: in case of metallic-coated aluminium, remove excess cleaner with clear water and a soft cotton cloth to avoid colour alterations and changes to the effect].

We recommend subsequent preservation using PV-Gard.

## 2. PV-GARD PRESERVATIVE

### Area of application:

To preserve the value of surfaces, apply preservative to painted and metallic-coated aluminium, glazed wood as well as hard, white and foiled uPVC. Once cleaned with Top-Clean Color, the preservative protects the surfaces from repeated contamination.

Note: Not suited for stainless steel and hand-oiled surfaces.

### Application:

Apply a thin film, allow to take effect for a short time and rub with a clean cloth.

## 3. SEAL CARE AGENT.

### Area of application:

Protection and care agent for EPDM seals in building elements, preserves their flexibility and prevents premature brittleness.

### Application:

Regularly clean seals using a mild conventional cleaner. Semi-annually apply seal care agent with a soft cloth and thoroughly remove excess product.

## 4. FITTING OIL

### Area of application:

Care agent for the maintenance of moving fittings. For easy-operation fittings, the oil leaves behind a protective film and eliminates squeaking and creaking sounds.

### Application:

Spray fittings with fitting oil once and remove excess oil with a clean cloth.

After that, operate the element several times to let the product take effect.

